



Ultra-Tech™
Gun-Grade Urethane Modified
Acrylic Elastomeric Sealant

Ultra-Tech™ elastomeric sealant is *the answer* to reliable caulking of butt joints, intersections, ends and corners in projects that use Plastic Components' PVC accessories.

This one-component, high-performance gun-grade sealant forms a flexible, airtight and water-resistant seal against moisture, and other environmental conditions. Durable Ultra-Tech offers superior adhesion and flexibility—with 800% elongation.

- Internally plasticized—no 'shiners' or paint discoloration
- Superior bonding to PVC and most other surfaces, including masonry, brick, concrete, wood, metal, marble, glass and ceramic tile
- Non-yellowing white sealant
Other colors available—Please contact customer service
- Mildew-resistant, reduces dirt pickup
- Paintable, soap and water cleanup
- Interior/exterior use

Technical Data

Once cured, Ultra-Tech exceeds the requirements of the following:

- Federal Specification TTS-00230C, Type S, Class A
- ASTM C-920, Grade NS, Class 25
- ASTM C-834, Type OP, -18° C


Use Ultra-Tech to caulk the butt joints, ends, angles, corners and intersections of Plastic Components' PVC accessories at time of installation.

Installation Guidelines

Surfaces to be caulked must be dry and free of all dirt, dust, mildew, oil or other contaminants. Apply Ultra-Tech only when surface and air temperatures are above 40° F and rising. Do not apply on surfaces that exceed 140° F, or when rain is expected.

Application: Cut nozzle at 45° angle. Cured bead should be between 1/8" and 1/2". Use backer rod for gaps larger than 1/2". Smooth bead with moistened cloth. Clean tools with soap and water. Allow 4 to 6 hours cure time before painting. Not intended for areas that will be submerged in water.

KEEP FROM FREEZING. KEEP OUT OF REACH OF CHILDREN.



Ultra-Tech™
Gun-grade Elastomeric Sealant

Product Number	Description	Tubes per Box
PC-ULTW	White, Gun-grade Urethane Modified Acrylic Sealant for use with Plastic Components' PVC accessories	(12) 10.1 oz each (299 mL)

Contact customer service for additional colors.

Limited Warranty

Manufacturer warrants that this product, provided it is properly stored and applied, will never crack, peel or separate. If a failure occurs, return proof of purchase for replacement. Manufacturer shall not be held liable for damages in excess of the purchase price. This is the sole and exclusive remedy and liability for defects or failure of this product. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES; WRITTEN OR ORAL, STATUTORY, EXPRESSED OR IMPLIED; INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS.

Distributed by



*...en español
al dorso*