

# Exterior Insulated Finishes

Section: 07240

## Two-Piece Hard Coat EIFS Casing Bead/STARTER TRAC®

Product Number	Dimension A	Dimension B	Pieces Per Box
SC-1-25	1" (25 mm)	1/4" (6 mm)	50
SC-1-38	1" (25 mm)	3/8" (10 mm)	50
SC-1-50	1" (25 mm)	1/2" (13 mm)	50
SC-15-25	1-1/2" (38 mm)	1/4" (6 mm)	40
SC-15-38	1-1/2" (38 mm)	3/8" (10 mm)	40
SC-15-50	1-1/2" (38 mm)	1/2" (13 mm)	40
SC-2-25	2" (51 mm)	1/4" (6 mm)	30
SC-2-38	2" (51 mm)	3/8" (10 mm)	30
SC-2-50	2" (51 mm)	1/2" (13 mm)	30

10' (3 m) Lengths



Add suffix "WP" to order with weep holes.  
 Example: SCWP-1-25

### Application:

Two piece starter strip locks into the finish. Protects EPS from damage at critical areas, gives positive protection. Eliminates back wrapping and finish of hard-to-reach areas. Can also be used as a casing bead in high impact areas.

### Specification:

Starter Strip/Casing Bead will be Plastic Components, Inc. #\_\_\_\_\_. All exterior accessories shall conform to ASTM standards D1784, C1063 and D4216. All products shall be third party tested to meet ASTM standard D4216 and be Canadian Code Compliant. They shall be used where specified by the architect and installed per industry standards.

