

# Exterior Insulated Finishes

45 YEARS  
PLASTIC PC  
COMPONENTS

Section: 07240

## Vent Screen TRAC

| Product Number | Description  | Foam Thickness | Pieces Per Box |
|----------------|--|----------------|----------------|
| VST-50         | TRAC for EIFS systems with double row of drainage holes at the rear of the TRAC. 2" (51 mm) wide nailing flange with nail attachment holes set at 4" (102 mm) o.c. | 1/2" (13 mm)   | 35             |
| VST-58         |  | 5/8" (16 mm)   | 35             |
| VST-75         |  | 3/4" (19 mm)   | 30             |
| VST-1          |  | 1" (25 mm)     | 25             |
| VST-125        |  | 1-1/4" (31 mm) | 20             |
| VST-15         |  | 1-1/2" (38 mm) | 20             |
| VST-175        |  | 1-3/4" (44 mm) | 15             |
| VST-2          |  | 2" (51 mm)     | 15             |
| VST-225        |  | 2-1/4" (57 mm) | 15             |
| VST-25         |  | 2-1/2" (64 mm) | 15             |
| VST-275        |  | 2-3/4" (70 mm) | 10             |
| VST-3          |  | 3" (76 mm)     | 10             |

10' (3 m) Lengths



### Application:

A vent screen trac for use with EIFS systems. The VST has a double row of drainage holes that aid in carrying moisture away from the structure. Its 2" (51 mm) wide nailing flange, and nail holes set every 4" (102 mm) provide secure attachment. It also provides superior bond of base coat to foamboard.

### Specification:

Vent Screen Trac will be Plastic Components, Inc. #\_\_\_\_\_. All exterior accessories shall conform to ASTM standards D1784, C1063 and D4216. All products shall be third party tested to meet ASTM standard D4216 and be Canadian Code Compliant. They shall be used where specified by the architect and installed per industry standards.

