

Stucco and Plaster

Section: 09200

ULTRA-LATH® Plastic Lath

1/8" Self Furred Non-Rusting

Plastic Component's Ultra Lath is perfect for one-coat stucco systems – in strips for drainage with cement board systems – and in sheets as an underlayment for tile, with and without radiant heating.

- 1/8" self-furred
- Available in sheets and rolls for overall coverage – and in strips
- High compressive strength
- Unaffected by salt, moisture, chemicals in tile-setting products, etc.
- Safe on hands, easy to cut and handle

Sheets

Rustproof, self furred, damage-resistant ULTRA-LATH® sheets

Product Number	Description ULTRA-LATH®	Packaging	Qty Per Pallet
PDM2796	ULTRA-LATH® Plastic Lath Sheets - 27" x 96" (686 mm x 2.4 M)	10 sheets per bundle/180 sq.ft. per bundle	25 bundles per pallet/4500 sq.ft. per pallet

Rolls

Rustproof, self furred, damage-resistant ULTRA-LATH® rolls

Product Number	Description ULTRA-LATH®	Packaging	Qty Per Pallet
PDMR	ULTRA-LATH® Plastic Lath Rolls - 27" x 100' roll (686 mm x 30.5 M)	225 sq.ft. per roll	18 rolls per pallet/4050 sq.ft. per pallet

Strip Lath

Rustproof, self furred, damage-resistant ULTRA-LATH® strips

Product Number	Width	Length	Pieces Per Box
PDM3	3" (76 mm)	96" (2.4 M)	50
PDM4	4" (102 mm)	96" (2.4 M)	50
PDM6	6" (152 mm)	96" (2.4 M)	50
PDM8	8" (203 mm)	96" (2.4 M)	50

We recommend Plastic Components trims for applications using ULTRA-LATH® plastic lath.



Application:

For either exterior or interior vertical application; should only be used for non-rated assemblies. The self-furring ridges provide exceptional keying and are applied towards the substrate. ULTRA-LATH® is impervious to sand and any harsh chemicals found in Portland-based stucco. IT WILL NEVER RUST. It may be installed over any code approved substrate. Can not be used in horizontal soffit applications.

Specification:

ULTRA-LATH® Plastic Lath shall be Plastic Components, Inc. #_____. It shall be used where specified by the architect and installed per industry standards ASTM C1764. Meets ASTM 330.84 and ASTM 330.84b.

PLASTIC PC™
COMPONENTS inc.

800.327.7077 ■ Fax 305.887.2452
www.plasticcomponents.com