## **Drywall Accessories**

Section: 09260

## **"F" Molding**

| Product<br>Number | Description  | Dimension<br>A     | Dimension<br>B  | Dimension<br>C    | Pieces<br>per Box |
|-------------------|--|--------------------|-----------------|-------------------|-------------------|
| 250-50            | "F" Molding.<br>May be used in<br>either drywall<br>or acoustical ap-<br>plications.<br>Can be laminated<br>for vinyl wall<br>covering<br>application. | 1-1/16"<br>(27 mm) | 1/2"<br>(13 mm) | 1-1/2"<br>(38 mm) | 50                |
| 250-58            |  | 1-3/16"<br>(30 mm) | 1/2"<br>(13 mm) | 1-1/2"<br>(38 mm) | 50                |
| 251-50            |  | 1"<br>(25 mm)      | 1"<br>(25 mm)   | 1-1/2"<br>(38 mm) | 50                |

10' (3 m) Lengths

## **Application:**

Outside corner. May be used in either drywall or acoustical applications. Can be laminated for vinyl wall covering application.

## **Specifications:**

"F" Molding shall be Plastic Components Inc. #\_\_\_\_\_. All drywall accessories shall conform to ASTM standards D3678 and C1047. All products shall be third party tested to meet ASTM standard D4216 and be Canadian Code Compliant. Finish compatible with drywall mud and all paint finishes. They shall be used where specified by the design authority and installed per industry standards.







2022