

CI/EIFS/Hard Coat

Section: 07240

EIFS Reveal Intersection

Product Number	Width	Depth	Piezas por Caja
2225	1/2" (13 mm)	1/2" (13 mm)	25
2226	1" (25 mm)	1/2" (13 mm)	25
2227	3/4" (19 mm)	1/2" (13 mm)	25
2228	3/8" (10 mm)	1/2" (13 mm)	25
2229	5/8" (16 mm)	1/2" (13 mm)	25
2235	1-1/2" (38 mm)	1/2" (13 mm)	25
2236	2" (51 mm)	1/2" (13 mm)	25
2237	3" (76 mm)	1/2" (13 mm)	25
2239	4" (102 mm)	1/2" (13 mm)	25

To order, add product suffix. Example: 2225C (for Cross), 2225T (for "T"), 2225A (for Angle), 2225EC (for End Closure), 22250C (for Outside Corner) or 22251C (for Inside Corner).

Contact customer service at (800) 327-7077 for lead time.


Application:

These factory thermal welded, surface mounted intersections eliminate the costly and time consuming need to field cut intersections.


Specifications:

EIFS Reveal Intersection shall be Plastic Components #_____. All exterior accessories shall meet ASTM standards D1784, C1063 and D4216, shall be third party tested and Canadian Code Compliant. They shall be used where specified by the design authority and installed per industry standards.

**Cross
(C)**



**"T"
(T)**




**Angle
(A)**




**End
Closure
(EC)**



**Inside
Corner
(IC)**



**Outside
Corner
(OC)**



The base coat mesh should be lapped over the top of the perforated flanges and across all butt joints.