

CI/EIFS/Hard Coat

Section: 07240

Two-Piece Hard Coat EIFS Casing Bead/STARTER TRAC®

Product Number	Dimension A	Dimension B	Pieces Per Box
SC-1-25	1" (25 mm)	1/4" (6 mm)	50
SC-1-38	1" (25 mm)	3/8" (10 mm)	50
SC-1-50	1" (25 mm)	1/2" (13 mm)	50
SC-15-25	1-1/2" (38 mm)	1/4" (6 mm)	40
SC-15-38	1-1/2" (38 mm)	3/8" (10 mm)	40
SC-15-50	1-1/2" (38 mm)	1/2" (13 mm)	40
SC-2-25	2" (51 mm)	1/4" (6 mm)	30
SC-2-38	2" (51 mm)	3/8" (10 mm)	30
SC-2-50	2" (51 mm)	1/2" (13 mm)	30

10' (3 m) Lengths

Add suffix "WP" to order with weep holes.
Example: SCWP-1-25



Application:

Two piece starter strip locks into the finish. Protects EPS from damage at critical areas, gives positive protection. Eliminates back wrapping and finish of hard-to-reach areas. Can also be used as a casing bead in high impact areas.

Specification:

Starter Strip/Casing Bead will be Plastic Components, Inc. #_____. All exterior accessories shall meet ASTM standards D1784, C1063, C1861 and D4216, shall be third party tested and Canadian Code compliant. They shall be used where specified by the design authority and installed per industry standards.

