

Direct Applied Finishes

Section: 07240

Vent Screen TRAC

Product Number	Dimensions/Descriptions	Foam Thickness	Pieces Per Box
VST-50	Trac for DEFS systems with double row of drainage holes at the rear of the TRAC. 1-1/8" (29 mm) return face flange.	1/2" (13 mm)	35
VST-58	4-hole pattern for superior bond of base coat to foam board. 2" (51 mm) wide nailing flange, with nail attachment holes set at 4" (102 mm) o.c.	5/8" (16 mm)	35

10' (3 m) Lengths

Please measure Foam Thickness Inside to inside



Application:

A vent screen trac for use with Direct Applied systems. The VST has a double row of drainage holes that aid in carrying moisture away from the structure. Its 2" (51 mm) wide nailing flange, and nail holes set every 4" (102 mm) o.c. provide secure attachment. It also provides superior bond of base coat to foam board.

Specification:

Vent Screen Trac will be Plastic Components, Inc. #_____. All exterior accessories shall meet ASTM standards D1784, C1063, C1861 and D4216, shall be third party tested and Canadian Code compliant. They shall be used where specified by the design authority and installed per industry standards.



The base coat mesh should be lapped over the top of the perforated flanges and across all butt joints.

800.327.7077 ■ Fax 305.887.2452
www.plasticcomponents.com