Stucco and Plaster



ULTRA-LATH PLUS® Plastic Lath 1/4" Self-Furred Rustproof Plastic Lath Complies with FLORIDA BUILDING CODE

Sheets Rustproof, self furred, damage-resistant Ultra-Lath Plus® sheets of plastic lath

Product Number	Description ULTRA-LATH PLUS [®] Plastic Lath	Packaging	Qty per Pallet
PDM2796-25	Plastic Lath Sheets - 27" x 96" (686 mm x 2.4 m) Plastic Lath Sheets	10 sheets per bundle	20 bundles per pallet 3600 sq.ft. (334.45 m ²) per bundle
PDM2796PB-25	27" x 96" (686 mm x 2.4 m) Backed with asphalt impregnated Type 1, grade D, Style 2 paper with standard offset	180 sq.ft. (16.8 m²) per bundle	

Rol	IS	Rustproof, self furred	d, damage-resistant Ultra-Lath Plus® rolls of plastic lath
-----	----	------------------------	--

Product Number	Description ULTRA-LATH PLUS [®] Plastic Lath	Packaging	Qty per Pallet
PDMR-25	ULTRA-LATH PLUS® Plastic Lath Rolls - 27" x 75' roll (686 mm x 22.9 m)	168 sq.ft. (15.6 m²) per roll	18 rolls per pallet/3024 sq.ft. (281 m ²) per pallet

Application: ULTRA-LATH PLUS® is designed for exterior or interior vertical or horizontal application. It's 1/4" self-furring ridges provide exceptional keying and should be applied with the ridges toward the substrate. ULTRA-LATH PLUS® meets ASTM C1764, C1788, C1780, C1063, C1861 and C1787 and is impervious to sand and any harsh chemicals found in portland based stucco. IT WILL NEVER RUST. It may be installed over any code approved substrate. ULTRA-LATH PLUS® now complies with 2020 FL Building Code and Metro Dade County HVHZ requirements for Impact and Cyclic performance (TAS 201, 202, 203) and is recognized by IAPMO Uniform Evaluation Services report #0284 as code compliant to the 2009 and 2012 International Building Code and Institute for Research for Construction (Canada)

Specifications: ULTRA-LATH PLUS® shall be Plastic Components Inc. . It shall be used where specified by the design authority and installed per industry standards. ULTRA-LATH PLUS® now complies with 2020 FL Building Code and Metro Dade County HVHZ requirements for Impact and Cyclic performance (TAS 201, 202, 203) and meets ASTM C1764, C1780, C1063, C1787, C1861 and C1788. Meets ASTM 330.84 and ASTM 330.84b.

Strip Lath Plus™	Rustproof, self furred, damage-resistant Ultra-Lath Plus® strips of plastic lath
------------------	---

Product Number	Width	Length	Pieces per Box
PDM3-25	3" (76 mm)	96" (2.4 m)	50
PDM4-25	4" (102 mm)	96" (2.4 m)	50
PDM6-25	6" (152 mm)	96" (2.4 m)	50
PDM8-25	8" (203 mm)	96" (2.4 m)	35

We recommend Plastic Components trims for applications using ULTRA-LATH PLUS® Plastic Lath.











2022