Lumber, Building Materials

Ultra Roof Mat[™]

Product Number	Thickness	Dimensions	Coverage	Rolls per Pallet
URM-36	.361" (9.16 mm)	Roll length/width 61.5' x 39" (18.75 m x 99.06 cm)	200 sf (18.58 m²)	18

Application:

Plastic Components' ULTRA ROOF MAT[™], our new roof ventilation mat, creates a cavity for air to flow in multiple directions under roofing material and the sheathing beneath it.

Ultra ROOF MAT features a thin nylon matrix profile that prolongs the life of the roof structure and membrane by reducing the damage caused by water and moisture – including mildew, mold and corrosion/deterioration of the roofing material. It's made of extremely flexible, heat-resistant material that conforms to any contoured surface or roofing material such as cedar, metal, tile, etc. – perfect for residential and commercial applications.

NOT RECOMMENDED FOR MASONRY or STONE VENEER APPLICATIONS.



Creates cavity for air flow in multiple directions





BENEFITS

- Withstands extreme heat
- Lightweight, easy to handle
- Adds to LEED points
- Reduces sound transmission
- Creates open space for added ventilation
- Prolongs the life of the roof membrane and structure
- Creates permanent thermal break between roofing and sheathing materials
- Flexible conforms to any type of contoured roof







305.885.0561 = 800.327.7077 www.plasticomponents.com