





for Fiber Cement Board

# Plastic Components

Florida-based **Plastic Components** is the originator and designer of many innovative trims, and since 1969, has manufactured quality plastic trims and accessories for the construction industry.

We develop high-quality plastic products that resolve problems created by standard metal.



Our nearly 700 line items include corner beads, control joints, vents, slip joints, reveals, and more for applications such as continuous insulation and exterior insulated finish systems (CI/EIFS), direct applied (DEFS), stucco and drywall. We offer the most complete line of PVC accessories for EIFS in the industry.

From freezing cold to extreme heat, Plastic Components' PVC products deliver optimal results – good looks, easy handling, moisture management, reduced labor costs and superior field performance.

Warnock Hersey

Our trims are tested and listed with Intertek

Testing Services/Warnock Hersey to meet or exceed the strict standards set by ASTM.



#### **PVC Accessories for Fiber Cement Board**

Manage moisture and get a better finish with our rustproof, aethestic reveals and trims for 1/2" and 5/16" board. These trims create pleasing lines while moving moisture away from the structure. And meet ASTM standards D4216, D1784 and C1861.

**UV Resistant – Paintable for Design Flexibility!** 



Trims for Fiber Cement Board

Manufacturers of PVC Accessories for Stucco/Plaster, CI/EIFS, DEFS & Drywall

# One-piece Paintable Reveals & Vents

## for 1/2 and 5/16 inch Fiber Cement Board



Plastic Components' one-piece aesthetic reveals improve the look of your building. And quickly and easily create consistent, decorative open space between boards.

- Made of Rustproof PVC
- UV resistant Paintable
- Four reveal dimensions for 1/2" and 5/16" fiber cement board
- Reveals, vents meet ASTM standards D4216, D1784 and C1861



**PIECES** 



PRODUCT NUMBER	AESTHETIC REVEAL DIMENSION	PIECES PER BOX	
for 1/2" (13 mm) FIBER CEMENT BOARD SYSTEMS			
707-50FCT	1/2" (13 mm)	35	
708-50FCT	3/4" (19 mm)	35	
709-50FCT	1" (25 mm)	35	
711-50FCT	2" (51 mm)	35	
for 5/16" (8 mm) FIBER CEMENT BOARD SYSTEMS			
707-516FCT	1/2" (13 mm)	35	
708-516FCT	3/4" (19 mm)	35	
709-516FCT	1" (25 mm)	35	
711-516FCT	2" (51 mm)	35	

10' (3 m) Lengths

**VENT AREA/** 

#### **Vents for Fiber Cement Board (FCB)**

**PRODUCT** 

### 3/8" (10 mm) REVEAL • 10 ft (3 m) Lengths

NUMBER	AIR FLOW per lillear it	PER BUX
for 5/16" (8 mm) FIBER CEMENT BOARD · 3/8" REVEAL		
548-516FCT	<b>2-5/8" (67 mm)</b> 14 sq. in. (9,033 sq. mm)	13
3548-516FCT	3" (76 mm) 15 sq. in. (9,678 sq. mm)	13
4548-516FCT	4" (102 mm) 16 sq. in. (10,323 sq. mm)	13
6548-516FCT	6" (152 mm) 18 sq. in. (11,614 sq. mm)	10

PRODUCT NUMBER	VENT AREA/ AIR FLOW per linear ft	PIECES PER BOX	
CONTINUOL	CONTINUOUS SOFFIT VENT · 3/8" REVEAL		
300	2-5/8" (67 mm) 14 sq. in. (9,033 sq. mm)	50	
301	1-3/4" (44 mm) 7 sq. in. (4,516 sq. mm)	50	
3300	3" (76 mm) 15 sq. in. (9,678 sq. mm)	35	
4300	4" (102 mm) 16 sq. in. (10,323 sq. mm)	35	
6300	6" (152 mm) 18 sq. in. (11,614 sq. mm)	30	



Caulk all butt joints, intersections and ends at the time of installation with an elastomeric sealant, such as Plastic Components' Tower Tech<sup>2TM</sup> (PC-TS00215).

9051 NW 97 Terrace • Miami, Florida 33178 • 305/885-0561 • 800/327-7077 • FAX 305/887-2452

# Trims for 1/2 and 5/16 inch Fiber Cement Board

Control Moisture · Rustfree, UV Resistant · Paintable



Trims for 1/2" and 5/16" Fiber Cement Board

**Inside and Outside Corner Bead** 

Consistent angles, even, impact-resistant corners

**Starter Trac** Positive slope moves moisture out, away from building

**Z Flashing Angled for moisture control.** Aligns horizontal boards.

H Trim Better than caulk for concealing vertical joints



PRODUCT	DESCRIPTION	PIECES
NUMBER	FOR FIBER CEMENT BOARD "FCB"	PER BOX

INSIDE/OUTSIDE CORNER BEAD		
2223	1-1/2" x 1-1/2"	50
	(38 mm x 38 mm)	

	Z FLASHING	
PCZ50	for 1/2" (13 mm) FCB	50
PCZ516	for 5/16" (8 mm) FCB	50

	WEEPED STARTER TRAC™	
CB1050-WP	for 1/2" (13 mm) FCB	50
CB10516-WP	for 5/16" (8 mm) FCB	50

	H TRIM	
2232-38	for 3/8" (10 mm) FCB	50
2232-50	for 1/2" (13 mm) FCB	50
2232-516	for 5/16" (8 mm) FCB	50





























Manufacturers of PVC Accessories for Stucco/Plaster, CI/EIFS, DEFS & Drywall

9051 NW 97 Terrace · Miami, Florida 33178 305/885-0561 · FAX 305/887-2452 800/327-7077

FCB0923